



Products specification/Information

EDEL SOCCER 5 XP - 32mm -2.0

A	Name of product Sports application	EDEL SOCCER 5 XP - 32mm - 2.0 Football, Soccer
B	Producer Production process	EDEL GRASS B.V. - Genemuiden - The Netherlands tufted, cut pile
C	Pile material Yarn Dtex Cross-section of tapes Colour Line colour UV-stability Light fastness Colour fastness	Thiolon® PE 10000 XP PRO yarn, fibrillated + MS EG polyethylene yarn monofilament, knit-de-knit, thermofixated micro curl environment friendly, UV-stabilised 11000/1 Dtex + 8500/12 Dtex width : 12 mm / 0.55 mm, ±5% thickness : 100 µm / 205 µm, ±5% field green/summergreen white/yellow DIN 53387 meets 6000 hours W.O.M. test >7 on blue scale 1-8 >4 on gray scale 1-5
D	Primary backing Coating Water permeability	Thiobac® polypropylene glas reinforced, UV-stabilised, total weight ± 335 gr/m ² Carboxylated (SBR) latex, appr. 1444 gr/m ² with 4mm perforation holes > 180 mm/h
E	Product details Pile height Total construction height Pile weight Total weight Gauge Stitch per m ¹ linear Stitch per m ² Filaments per m ²	appr. 32 mm ±10% appr. 34 mm ±10% appr. 2830 gr/m ² ±10% appr. 4609 gr/m ² ±10% 3/8" 190 ±10 19950 ±10% 518700 ±10%
F	Infill Stabilizing infill Amount Performance infill Amount	N.A N.A
G	Installation method Roll width Roll length Joints/seams Line marking	loose laid on bound or unbound sub-base with loose laid shockpad or in situ E-layer 4 m ¹ (± 2 cm) according to installation schedule the seams in the turf are joined with a reinforcing tape type 220 glued to the back of the turf tufted-in or to be laid in by installation

The above data are subject to modifications based on technical improvements or company-internal developments. All data are higher than the DIN-standards. All figures are average values and can vary slightly.